



G-Biosciences, St Louis, MO, USA | 1-800-628-7730 | 1-314-991-6034 | technical@GBiosciences.com

A Geno Technology, Inc. (USA) brand name

Safety Data Sheet

Cat. # 786-1625

SpinOUT™ G-Acryl 600, 10ml

Size: 5 columns



think proteins! think G-Biosciences!

www.GBiosciences.com



SpinOUT G-Acryl 600

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 07/01/2019

Version: 1.1

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Product name : SpinOUT G-Acryl 600
Product code : 911S_912S_913S_914S_915S_916S
Synonyms : sephadex G25 fine 20-80
BIG No : 48721

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Laboratory chemical

1.3. Supplier

Geno Technology, Inc./ G-Biosciences
9800 Page Avenue
Saint Louis, 63132-1429 - United States
T 800-628-7730 - F 314-991-1504
technical@GBiosciences.com - www.GBiosciences.com

1.4. Emergency telephone number

Emergency number : Chemtrec **1-800-424-9300** (USA/Canada), **+1-703-527-3887** (Intl)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 H227 Combustible liquid

Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Signal word (GHS US) : Warning
Hazard statements (GHS US) : H227 - Combustible liquid
Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear protective gloves/protective clothing/eye protection/face protection.
P370+P378 - In case of fire: Use media other than water to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Common Name (Synonyms)	Product identifier	%	GHS US classification
ethanol	ethanol (ethyl alcohol) / ethanol, anhydrous, undenatured / ethyl alcohol	(CAS-No.) 64-17-5	10 - 50	Flam. Liq. 2, H225

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : If you feel unwell, seek medical advice.
First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

SpinOUT G-Acryl 600

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

First-aid measures after skin contact	: Rinse with water. Do not apply (chemical) neutralizing agents without medical advice. Soap may be used. Take victim to a doctor if irritation persists.
First-aid measures after eye contact	: Rinse with water. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply (chemical) neutralizing agents without medical advice. Take victim to an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Rinse mouth with water. Do not apply (chemical) neutralizing agents without medical advice. Call Poison Information Centre (www.big.be/antigif.htm). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after inhalation	: No effects known.
Symptoms/effects after skin contact	: No effects known.
Symptoms/effects after eye contact	: No effects known.
Symptoms/effects after ingestion	: No effects known.
Chronic symptoms	: No effects known.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Quick-acting ABC powder extinguisher. Class A foam extinguisher. Water (quick-acting extinguisher, reel). Water. Class A foam.
Unsuitable extinguishing media	: Quick-acting BC powder extinguisher. Quick-acting CO2 extinguisher.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
Explosion hazard	: DIRECT EXPLOSION HAZARD: Most organic solids are liable to dust explosion hazard. INDIRECT EXPLOSION HAZARD: Dust cloud can be ignited by a spark.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire	: Exposure to fire/heat: keep upwind. Exposure to fire/heat: have neighbourhood close doors and windows.
Firefighting instructions	: No specific fire-fighting instructions required.
Protection during firefighting	: Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment	: Gloves. Protective clothing. Dust cloud production: compressed air/oxygen apparatus.
Emergency procedures	: Mark the danger area. Prevent dust cloud formation, e.g. by wetting. Wash contaminated clothes.
Measures in case of dust release	: In case of dust production: keep upwind. Dust production: have neighbourhood close doors and windows.

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
----------------------	---

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment	: Contain released product, pump into suitable containers. Plug the leak, cut off the supply. Knock down/dilute dust cloud with water spray.
Methods for cleaning up	: Stop dust cloud by humidifying. Scoop solid spill into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SpinOUT G-Acryl 600

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Avoid raising dust. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Comply with the legal requirements. Clean contaminated clothing. Keep container tightly closed. Powdered form: no compressed air for pumping over.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store in a well-ventilated place. Keep cool.
- Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources. ignition sources.
- Information on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents. water/moisture.
- Storage area : Store in a cool area. Store in a dry area. Keep container in a well-ventilated place. Meet the legal requirements.
- Special rules on packaging : SPECIAL REQUIREMENTS: closing. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SpinOUT G-Acryl 600	
No additional information available	
ethanol (64-17-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH STEL (ppm)	1000 ppm

8.2. Appropriate engineering controls

- Appropriate engineering controls : Ensure good ventilation of the work station.
- Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Protective gloves against chemicals (EN374)

Eye protection:

Safety glasses. In case of dust production: protective goggles

Skin and body protection:

Protective clothing

Respiratory protection:

Dust production: dust mask with filter type P1

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Appearance : Solid. Powder.
- Color : White
- Odor : No data available
- Odor threshold : No data available
- pH : No data available
- Melting point : Not applicable
- Freezing point : No data available
- Boiling point : No data available

SpinOUT G-Acryl 600

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Flash point	: 65 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20 °C	: Not applicable
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

VOC content	: 0 %
-------------	-------

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

ethanol (64-17-5)	
LD50 oral rat	10740 mg/kg body weight (Rat; OECD 401: Acute Oral Toxicity; Experimental value)
LD50 dermal rabbit	> 16000 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	> 20 mg/l (4 h, Rat, Inhalation)

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified

ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity	: Not classified
-----------------------	------------------

Specific target organ toxicity – single exposure	: Not classified
--	------------------

SpinOUT G-Acryl 600

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Specific target organ toxicity – repeated exposure	: Not classified
Aspiration hazard	: Not classified
Viscosity, kinematic	: No data available
Symptoms/effects after inhalation	: No effects known.
Symptoms/effects after skin contact	: No effects known.
Symptoms/effects after eye contact	: No effects known.
Symptoms/effects after ingestion	: No effects known.
Chronic symptoms	: No effects known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
Ecology - air	: Not included in the list of substances which may contribute to the greenhouse effect (IPCC). Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).

ethanol (64-17-5)	
LC50 fish 1	14200 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value)
EC50 Daphnia 1	9300 mg/l (48 h, Daphnia magna, Pure substance)

12.2. Persistence and degradability

SpinOUT G-Acryl 600	
Persistence and degradability	Biodegradability in water: no data available.
ethanol (64-17-5)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. No (test)data on mobility of the substance available.
Biochemical oxygen demand (BOD)	0.8 - 0.967 g O ₂ /g substance
Chemical oxygen demand (COD)	1.7 g O ₂ /g substance
ThOD	2.1 g O ₂ /g substance
BOD (% of ThOD)	0.43

12.3. Bioaccumulative potential

SpinOUT G-Acryl 600	
Bioaccumulative potential	No bioaccumulation data available.
ethanol (64-17-5)	
BCF fish 1	1 (Other, 72 h, Cyprinus carpio, Static system, Fresh water, Read-across)
Log Pow	-0.35 (Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 24 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

12.4. Mobility in soil

SpinOUT G-Acryl 600	
Ecology - soil	No (test)data on mobility of the substance available.
ethanol (64-17-5)	
Surface tension	0.0245 N/m (20 °C)
Ecology - soil	Highly mobile in soil.

12.5. Other adverse effects

No additional information available

SpinOUT G-Acryl 600

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 13: Disposal considerations

13.1. Disposal methods

- Waste treatment methods : Waste treatment methods.
- Product/Packaging disposal recommendations : Remove waste in accordance with local and/or national regulations. Remove to an authorized waste treatment plant.
- Additional information : Can be considered as non hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Not applicable

Transportation of Dangerous Goods

Not applicable

Transport by sea

Not applicable

Air transport

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

ethanol (64-17-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

National regulations

ethanol (64-17-5)

Listed on IARC (International Agency for Research on Cancer)

15.3. US State regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H227	Combustible liquid

SpinOUT G-Acryl 600

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

NFPA health hazard


: 0 - Materials that, under emergency conditions, would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard

: 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.