



Safety Data Sheet

Cat. # BTNM-0077

Triton X-100, 2%, 20 mL

Size: 20 mL





Triton X-100, 2%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 11/10/2015

Revision date: 05/11/2017

Version: 7.1

SECTION 1: Identification

1.1. Identification

Product form : Substance
Substance name : Triton X-100, 2%
Product code : T106
Formula : C34H62O12
Synonyms : 2-[4-(2,4,4-trimethylpentan-2-yl)phenoxy]ethanol / 4(1,1,3,3-tetramethylbutyl)phenyl polyethylene glycol / poly(oxy-1,2-ethanediyl), alpha-(4-(1,1,3,3-tetramethylbutyl)phenyl)-omega-hydroxy- / polyethylene glycol tert-octylphenyl ether / tert-octylphenoxy polyethoxyethanol / TRITON X-100
BIG No : 18801

1.2. Recommended use and restrictions on use

Use of the substance/mixture : Surfactant

1.3. Supplier

Geno Technology, Inc./ G-Biosciences
9800 Page Avenue
Saint Louis, 63132-1429 - United States
T 800-628-7730 - F 314-991-1504
technical@GBiosciences.com - www.GBiosciences.com

1.4. Emergency telephone number

Emergency number : Chemtrec **1-800-424-9300** (USA/Canada), **+1-703-527-3887** (Intl)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Acute toxicity (oral) Category 4 H302 Harmful if swallowed
Hazardous to the aquatic environment - Acute Hazard Category 2 H401 Toxic to aquatic life
Hazardous to the aquatic environment - Chronic Hazard Category 2 H411 Toxic to aquatic life with long lasting effects
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning
Hazard statements (GHS US) : H302 - Harmful if swallowed
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects
Precautionary statements (GHS US) : P264 - Wash hands, forearms and face thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P273 - Avoid release to the environment.
P301+P312 - If swallowed: Call a poison center or doctor if you feel unwell
P330 - Rinse mouth.
P391 - Collect spillage.
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

Triton X-100, 2%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 3: Composition/Information on ingredients

3.1. Substances

Substance type : Polymer
Name : Triton X-100, 2%

Name	Common Name (Synonyms)	Product identifier	%	GHS US classification
polyethyleneglycol para-(1,1,3,3-tetramethylbutyl)phenyl ether	2-[4-(2,4,4-trimethylpentan-2-yl)phenoxy]ethanol / 4(1,1,3,3-tetramethylbutyl)phenyl polyethylene glycol / poly(oxy-1,2-ethanediyl), alpha-(4-(1,1,3,3-tetramethylbutyl)phenyl)-omega-hydroxy- / polyethylene glycol tert-octylphenyl ether / tert-octylphenoxypolyethoxyethanol / TRITON X-100	(CAS-No.) 9002-93-1	2 - 5	Acute Tox. 4 (Oral), H302 Eye Irrit. 2, H319 Aquatic Acute 2, H401 Aquatic Chronic 2, H411

Full text of hazard classes and H-statements : see section 16

3.2. Mixtures

Not applicable

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures general : Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

First-aid measures after inhalation : Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

First-aid measures after skin contact : Rinse with water. Soap may be used. Take victim to a doctor if irritation persists.

First-aid measures after eye contact : Rinse immediately with plenty of water for 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Do not apply neutralizing agents. Take victim to an ophthalmologist.

First-aid measures after ingestion : Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Call Poison Information Centre (www.big.be/antigif.htm). Consult a doctor/medical service if you feel unwell. Ingestion of large quantities: immediately to hospital.

4.2. Most important symptoms and effects (acute and delayed)

Potential Adverse human health effects and symptoms : Harmful if swallowed. Non-toxic in contact with skin (LD50 skin > 5000 mg/kg). Slightly irritant to skin. Causes serious eye irritation. Caution! Substance is absorbed through the skin.

Symptoms/effects after skin contact : Slight irritation.

Symptoms/effects after eye contact : Irritation of the eye tissue.

Symptoms/effects after ingestion : AFTER INGESTION OF HIGH QUANTITIES: Nausea. Vomiting. Diarrhoea.

Chronic symptoms : No effects known.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Quick-acting ABC powder extinguisher. Quick-acting BC powder extinguisher. Quick-acting class B foam extinguisher. Quick-acting CO2 extinguisher. Class B foam (alcohol-resistant). Water spray if puddle cannot expand.

Unsuitable extinguishing media : Water (quick-acting extinguisher, reel); risk of puddle expansion. Water; risk of puddle expansion.

5.2. Specific hazards arising from the chemical

Fire hazard : DIRECT FIRE HAZARD: Not easily combustible. INDIRECT FIRE HAZARD: Temperature above flashpoint: higher fire/explosion hazard.

5.3. Special protective equipment and precautions for fire-fighters

Precautionary measures fire : Exposure to fire/heat: keep upwind. Exposure to fire/heat: seal off low-lying areas. Exposure to fire/heat: have neighbourhood close doors and windows.

Firefighting instructions : No specific fire-fighting instructions required.

Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

Triton X-100, 2%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Gloves. Safety glasses. Protective clothing.
Emergency procedures : Mark the danger area. No naked flames. Wash contaminated clothes.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Contain released product, pump into suitable containers. Plug the leak, cut off the supply.
Methods for cleaning up : Take up liquid spill into inert absorbent material, e.g.: sand, earth, vermiculite. Scoop absorbed substance into closing containers. Clean contaminated surfaces with an excess of water. Wash clothing and equipment after handling.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Keep away from naked flames/heat. In finely divided state: use spark-/explosionproof appliances. Finely divided: keep away from ignition sources/sparks. Carry operations in the open/under local exhaust/ventilation or with respiratory protection. Comply with the legal requirements. Clean contaminated clothing. Keep container tightly closed.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool.
Storage temperature : 15 - 25 °C
Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources.
Information on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents. reducing agents. (strong) acids. (strong) bases.
Storage area : Meet the legal requirements.
Special rules on packaging : SPECIAL REQUIREMENTS: closing. correctly labelled. meet the legal requirements. Secure fragile packagings in solid containers.
Packaging materials : SUITABLE MATERIAL: metal. glass. MATERIAL TO AVOID: copper. bronze.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Triton X-100, 2%

No additional information available

polyethyleneglycol para-(1,1,3,3-tetramethylbutyl)phenyl ether (9002-93-1)

No additional information available

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Materials for protective clothing:

GIVE EXCELLENT RESISTANCE: nitrile rubber

Hand protection:

Triton X-100, 2%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protective gloves against chemicals (EN374)

Eye protection:

Safety glasses

Skin and body protection:

Protective clothing

Respiratory protection:

Respiratory protection not required in normal conditions

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Color	: Light yellow
Odor	: Mild odour
Odor threshold	: No data available
pH	: 9.7
Melting point	: 6 °C
Freezing point	: No data available
Boiling point	: > 200 °C
Flash point	: 251 °C (Closed cup)
Relative evaporation rate (butyl acetate=1)	: < 1
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: < 1.33 hPa (20 °C)
Relative vapor density at 20 °C	: > 1
Relative density	: 1.007
Specific gravity / density	: 1007 kg/m ³
Solubility	: Soluble in water. Soluble in ethanol. Soluble in acetone. Soluble in aromatic hydrocarbons. Water: complete
Log Pow	: 4.86 (Estimated value)
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

Other properties : Gas/vapour heavier than air at 20°C. Clear. Slightly volatile. Basic reaction.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reacts with (strong) oxidizers and with (strong) reducers.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

Triton X-100, 2%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.6. Hazardous decomposition products

Hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Triton X-100, 2%	
LD50 oral rat	1800 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	8000 mg/kg (Rabbit, Literature study, Dermal)
ATE US (oral)	1800 mg/kg body weight
ATE US (dermal)	8000 mg/kg body weight

polyethyleneglycol para-(1,1,3,3-tetramethylbutyl)phenyl ether (9002-93-1)	
LD50 oral rat	1800 mg/kg (Rat, Literature study, Oral)
LD50 dermal rabbit	8000 mg/kg (Rabbit, Literature study, Dermal)
ATE US (oral)	1800 mg/kg body weight
ATE US (dermal)	8000 mg/kg body weight

Skin corrosion/irritation : Not classified
pH: 9.7
Serious eye damage/irritation : Not classified
pH: 9.7
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
Specific target organ toxicity – single exposure : Not classified
Specific target organ toxicity – repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : No data available
Potential Adverse human health effects and symptoms : Harmful if swallowed. Non-toxic in contact with skin (LD50 skin > 5000 mg/kg). Slightly irritant to skin. Causes serious eye irritation. Caution! Substance is absorbed through the skin.
Symptoms/effects after skin contact : Slight irritation.
Symptoms/effects after eye contact : Irritation of the eye tissue.
Symptoms/effects after ingestion : AFTER INGESTION OF HIGH QUANTITIES: Nausea. Vomiting. Diarrhoea.
Chronic symptoms : No effects known.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Toxic to aquatic life with long lasting effects. Toxic to aquatic life.
Ecology - air : Not included in the list of fluorinated greenhouse gases (Regulation (EU) No 517/2014). Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009).
Ecology - water : Harmful to crustacea. Toxic to fishes. pH shift.

Triton X-100, 2%	
LC50 fish 1	8.9 mg/l (96 h, Pimephales promelas, Literature study)
EC50 Daphnia 1	26 mg/l (48 h, Daphnia magna, Literature study)

polyethyleneglycol para-(1,1,3,3-tetramethylbutyl)phenyl ether (9002-93-1)	
LC50 fish 1	8.9 mg/l (96 h, Pimephales promelas, Literature study)
EC50 Daphnia 1	26 mg/l (48 h, Daphnia magna, Literature study)

Triton X-100, 2%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.2. Persistence and degradability

Triton X-100, 2%	
Persistence and degradability	Not readily biodegradable in water.
Chemical oxygen demand (COD)	2.19 mg/g
ThOD	2.16 g O ₂ /g substance
polyethyleneglycol para-(1,1,3,3-tetramethylbutyl)phenyl ether (9002-93-1)	
Persistence and degradability	Not readily biodegradable in water.
Chemical oxygen demand (COD)	2.19 mg/g
ThOD	2.16 g O ₂ /g substance

12.3. Bioaccumulative potential

Triton X-100, 2%	
Log Pow	4.86 (Estimated value)
Bioaccumulative potential	Potential for bioaccumulation ($4 \geq \text{Log Kow} \leq 5$).
polyethyleneglycol para-(1,1,3,3-tetramethylbutyl)phenyl ether (9002-93-1)	
Log Pow	4.86 (Estimated value)
Bioaccumulative potential	Potential for bioaccumulation ($4 \geq \text{Log Kow} \leq 5$).

12.4. Mobility in soil

Triton X-100, 2%	
Ecology - soil	No (test)data on mobility of the substance available.
polyethyleneglycol para-(1,1,3,3-tetramethylbutyl)phenyl ether (9002-93-1)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Waste treatment methods.
Product/Packaging disposal recommendations	: Do not discharge into drains or the environment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. In authorized incinerator equipped with flue gas scrubber with energy recovery. Dissolve or mix with a combustible solvent. May be discharged to wastewater treatment installation.
Additional information	: Hazardous waste according to Directive 2008/98/EC, as amended by Regulation (EU) No 1357/2014 and Regulation (EU) No 2017/997.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Dangerous for the environment	: Yes
Marine pollutant	: Yes



Other information	: No supplementary information available.
-------------------	---

Triton X-100, 2%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Transportation of Dangerous Goods

Transport by sea

Transport document description (IMDG) : UN 3082 environmentally hazardous substance, liquid, n.o.s., 9, III, MARINE POLLUTANT
UN-No. (IMDG) : 3082
Proper Shipping Name (IMDG) : environmentally hazardous substance, liquid, n.o.s.
Class (IMDG) : 9 - Miscellaneous dangerous substances and articles
Packing group (IMDG) : III - substances presenting low danger
EmS-No. (1) : F-A
EmS-No. (2) : S-F
Marine pollutant : Yes



Air transport

Transport document description (IATA) : UN 3082 Environmentally hazardous substance, liquid, n.o.s., 9, III
UN-No. (IATA) : 3082
Proper Shipping Name (IATA) : Environmentally hazardous substance, liquid, n.o.s.
Class (IATA) : 9 - Miscellaneous Dangerous Goods
Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Triton X-100, 2%

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

polyethyleneglycol para-(1,1,3,3-tetramethylbutyl)phenyl ether (9002-93-1)

Not listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Flag

XU - XU - indicates a substance exempt from reporting under the Chemical Data Reporting Rule, (40 CFR 711).

15.2. International regulations

CANADA

EU-Regulations

National regulations

No additional information available

15.3. US State regulations

SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 05/11/2017

Triton X-100, 2%

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H302	Harmful if swallowed
H319	Causes serious eye irritation
H401	Toxic to aquatic life
H411	Toxic to aquatic life with long lasting effects

NFPA health hazard


: 2 - Materials that, under emergency conditions, can cause temporary incapacitation or residual injury.

NFPA fire hazard

: 1 - Materials that must be preheated before ignition can occur.

NFPA reactivity

: 0 - Material that in themselves are normally stable, even under fire conditions.



SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.