



G-Biosciences, St Louis, MO, USA ♦ 1-800-628-7730 ♦ 1-314-991-6034 ♦ technical@Gbiosciences.com

A Geno Technology, Inc. (USA) brand name

Safety Data Sheet

Co-NTA Spin Plates

Cat. # 786-988



think proteins! think G-Biosciences!

www.GBiosciences.com



Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations
Date of issue: 2/25/2015 Revision date: 11/24/2025 Supersedes: 10/30/2025 Version: 12.0

SECTION 1 Identification

1.1. Product identifier

Product form : Mixture
Product name : Co-NTA Resin
Product code : 221C_223C_224C_225C_226C

1.2. Other means of identification

No additional information available

1.3. Recommended use of the chemical and restrictions on use

Use of the substance/mixture : Research and development

1.4. Supplier's details

G-Biosciences/ Geno Technology, Inc.
9800 Page Avenue
St. Louis, MO 63132-1429, USA
Tel.1-800-628-7730
www.GBiosciences.com

1.5. Emergency phone number

Emergency number : Chemtrec **1-800-424-9300** (USA/Canada), **+1-703-527-3887** (Intl)

SECTION 2 Hazard Identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquid, Category 2	H225	Highly flammable liquid and vapor.
Respiratory sensitization, Category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization, Category 1	H317	May cause an allergic skin reaction.
Germ cell mutagenicity, Category 2	H341	Suspected of causing genetic defects.
Carcinogenicity, Category 1A	H350	May cause cancer.
Hazardous to the aquatic environment — Acute Hazard, Category 3	H402	Harmful to aquatic life.
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	Harmful to aquatic life with long lasting effects.

Full text of H statements : see section 16

2.2. Label elements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Danger
Hazard statements (GHS US) : H225 - Highly flammable liquid and vapor
H317 - May cause an allergic skin reaction
H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled
H341 - Suspected of causing genetic defects.
H350 - May cause cancer.

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Precautionary statements (GHS US)

H402 - Harmful to aquatic life
H412 - Harmful to aquatic life with long lasting effects
: P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233 - Keep container tightly closed.
P240 - Ground/Bond container and receiving equipment.
P241 - Use explosion-proof equipment.
P242 - Use non-sparking tools.
P243 - Take action to prevent static discharges.
P261 - Avoid breathing dust, fume, gas, mist, vapors, spray.
P272 - Contaminated work clothing must not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear protective gloves, protective clothing, eye protection, face protection, and hearing protection.
P284 - Wear respiratory protection.
P302+P352 - If on skin: Wash with plenty of water.
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308+P313 - If exposed or concerned: Get medical advice/attention.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P333+P313 - If skin irritation or rash occurs: Get medical advice or attention.
P342+P311 - If experiencing respiratory symptoms: Call a poison center or doctor.
P362+P364 - Take off contaminated clothing and wash it before reuse.
P370+P378 - In case of fire: Use appropriate media to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P405 - Store locked up.
P501 - Dispose of contents and/or container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulations.

2.3. Hazards associated with known or reasonably anticipated uses

No additional information available

2.4. Hazards not otherwise classified

No additional information available

2.5. Unknown acute toxicity

No additional information available

SECTION 3 Composition/information on ingredients

3.1. Substances

Not applicable

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

3.2. Mixtures

Name	Common Name (Synonyms)	Product identifier	%	GHS US classification
ethanol	1-hydroxyethane / absolute alcohol / absolute ethanol / alcohol / alcohol 200 proof / alcohol C2 / alcohol, absolute / alcohol, anhydrous / alcohol, dehydrated / algrain / anhydrol / anydrol / APEXA / bioethanol / BIO-Fire / cologne spirit / cologne spirits / ECO-Fire / ethanol / ethanol 200 proof / ethanol, absolute / ethicap / ethyl alcohol / ethyl alcohol, anhydrous / ethyl hydrate / ethyl hydroxide / ethylic alcohol / fermentation alcohol / grain alcohol / hydrated oxide of ethyl / IMS grades (=ethanol) / industrial alcohol / jaysol / jaysol S / methyl carbinol / methylated spirit (=ethanol) / molasses alcohol / neutral spirits / potable spirits / potato alcohol / proof spirits / rectified spiritus / SD alcohol 23-hydrogen / silent spirit / spirit / spirit of wine / spirits of wine / tecsol / Tecsol C	CAS-No.: 64-17-5	10 – 50	Flam. Liq. 2, H225 Carc. 1A, H350

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Common Name (Synonyms)	Product identifier	%	GHS US classification
cobalt(II)sulfate, heptahydrate (Note 1)	cobalt sulfate, heptahydrate / cobalt sulphate, heptahydrate / cobaltous sulfate, heptahydrate / sulfuric acid, cobalt(II)salt, heptahydrate	CAS-No.: 10026-24-1	< 2	Acute Tox. 4 (Oral), H302 Resp. Sens. 1, H334 Skin Sens. 1, H317 Muta. 2, H341 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Note 1: Note 1 : The concentration stated or, in the absence of such concentrations, the generic concentrations set out in this Regulation are the percentages by weight of the metallic element calculated with reference to the total weight of the mixture.

Full text of hazard classes and H-statements : see section 16

SECTION 4 First aid measures

4.1. Description of necessary first-aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible). IF exposed or concerned: Get medical advice/attention.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. If experiencing respiratory symptoms: Call a poison center or a doctor.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Specific treatment (see supplemental first aid instruction on this label). Wash contaminated clothing before reuse. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse immediately with plenty of water. Obtain medical attention if pain, blinking or redness persists. Rinse eyes with water as a precaution.
First-aid measures after ingestion	: Rinse mouth. Do NOT induce vomiting. Obtain emergency medical attention. Call a poison center/doctor/physician if you feel unwell.
Self protection of the first-aider	: First aid workers will be equipped with suitable personal protective equipment.

4.2. Most important symptoms/effects, acute and delayed

Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/effects	: Suspected of causing genetic defects.
Symptoms/effects after inhalation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer by inhalation.
Symptoms/effects after skin contact	: May cause an allergic skin reaction.
Symptoms/effects after eye contact	: None under normal conditions.
Symptoms/effects after ingestion	: None under normal conditions.
Chronic symptoms	: May damage fertility or the unborn child.

4.3. Indication of immediate medical attention and special treatment needed, if necessary

Other medical advice or treatment	: Treat symptomatically.
-----------------------------------	--------------------------

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Foam. Dry powder. Carbon dioxide. Water spray. Sand.
Unsuitable extinguishing media : Do not use a heavy water stream.

5.2. Specific hazards arising from the chemical

Fire hazard : Highly flammable liquid and vapor.
Explosion hazard : May form flammable/explosive vapor-air mixture.
Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment. Do not enter fire area without proper protective equipment, including respiratory protection.
Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection. Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6 Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. No open flames. No smoking. Stop leak if safe to do so. Notify authorities if product enters sewers or public waters. Absorb spillage to prevent material-damage.

For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid contact with skin and eyes. Evacuate unnecessary personnel. Only qualified personnel equipped with suitable protective equipment may intervene. Avoid breathing dust/fume/gas/mist/vapors/spray.

For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. Equip cleanup crew with proper protection. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area. Evacuate unnecessary personnel. Stop leak if safe to do so.
Environmental precautions : Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters. Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.2. Methods and materials for containment and cleaning up

For containment : Collect spillage. Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams. Stop leak, if possible without risk.
Methods for cleaning up : Take up liquid spill into absorbent material. Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials. Notify authorities if product enters sewers or public waters.
Other information : Dispose of materials or solid residues at an authorized site.

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 7 Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor. No open flames. No smoking. Use only non-sparking tools. Avoid breathing dust/fume/gas/mist/vapors/spray. Obtain special instructions before use. Use personal protective equipment as required. Do not handle until all safety precautions have been read and understood. Ground/bond container and receiving equipment. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Avoid contact with skin and eyes.
- Hygiene measures : Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reuse. Separate working clothes from town clothes. Launder separately. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.
- Additional hazards when processed : Handle empty containers with care because residual vapors are flammable.

7.2. Conditions for safe storage, including incompatibilities

- Technical measures : Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment.
- Storage conditions : Store in a well-ventilated place. Keep cool. Keep only in the original container in a cool, well ventilated place away from : Keep in fireproof place. Keep container tightly closed. Store locked up.
- Incompatible products : Strong bases. Strong acids.
- Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.
- Storage temperature : 4 °C
- Packaging materials : Store always product in container of same material as original container.

SECTION 8 Exposure controls/personal protection

8.1. Control parameters

ethanol (64-17-5)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH® TLV® STEL	1000 ppm
USA - Cal/OSHA - Occupational Exposure Limits	
Local name	Ethyl alcohol; ethanol
Cal/OSHA PEL (OEL TWA)	1900 mg/m ³
	1000 ppm
Regulatory reference	California Division of Occupational Safety and Health (Cal/OSHA) - Permissible Exposure Limit for Chemical Contaminants (Table AC-1)
USA - NIOSH - Occupational Exposure Limits	
Local name	Ethyl alcohol (Ethanol)
NIOSH REL 10h TWA	1000 ppm
Regulatory reference (US-NIOSH)	OSHA Annotated Table Z-1 (NIOSH Pocket Guide to Chemical Hazards (NPG))

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cobalt(II)sulfate, heptahydrate (10026-24-1)

USA - ACGIH - Occupational Exposure Limits

ACGIH® TLV® TWA	0.02 mg/m ³ (Inhalable fraction)
-----------------	---

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures, such as personal protective equipment

Personal protective equipment:

Avoid all unnecessary exposure.

Hand protection:

Protective gloves. Wear protective gloves.

Eye protection:

Chemical goggles or safety glasses. Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. In case of inadequate ventilation wear respiratory protection. [In case of inadequate ventilation] wear respiratory protection.

Personal protective equipment symbol(s):



Other information:

Do not eat, drink or smoke during use.

SECTION 9 Physical and chemical properties

9.1. Basic physical and chemical properties

Physical state	: Liquid
Color	: pink
Odor	: characteristic
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 65 °C
Flammability (solid, gas)	: Not applicable. Highly flammable liquid and vapor.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Viscosity, kinematic : No data available
Explosion limits : No data available
Particle characteristics : No data available

9.2. Data relevant with regard to physical hazard classes (supplemental)

No additional information available

SECTION 10 Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Highly flammable liquid and vapor.

10.2. Chemical stability

Stable under normal conditions. Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use. Not established.

10.4. Conditions to avoid

Avoid contact with hot surfaces. No flames, no sparks. Eliminate all sources of ignition. Direct sunlight. Extremely high or low temperatures. Open flame. Heat.

10.5. Incompatible materials

Strong acids. Strong bases.

10.6. Hazardous decomposition products

Hazardous decomposition products. fume. Carbon monoxide. Carbon dioxide. May release flammable gases.

SECTION 11 Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

ethanol (64-17-5)	
LD50 oral rat	10470 mg/kg body weight (OECD 401: Acute Oral Toxicity, Rat, Male / female, Experimental value, Oral, 14 day(s))
LD50 oral	8300 mg/kg body weight Animal: mouse
LD50 dermal rabbit	> 15800 mg/kg body weight (Rabbit, Experimental value, Dermal)
LC50 Inhalation - Rat	124.7 mg/l air (Equivalent or similar to OECD 403, 4 h, Rat, Male / female, Experimental value, Inhalation (vapours), 14 day(s))
LC50 Inhalation - Rat (Vapors)	116.9 mg/l Source: ECHA
ATE US (oral)	10470 mg/kg body weight
ATE US (vapors)	116.9 mg/l/4h
ATE US (dust, mist)	124.7 mg/l/4h

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cobalt(II)sulfate, heptahydrate (10026-24-1)	
LD50 oral rat	424 mg/kg body weight (Equivalent or similar to OECD 401, Rat, Male / female, Experimental value, Oral, 10 day(s))
LD50 dermal rat	> 2000 mg/kg body weight (OECD 402: Acute Dermal Toxicity, 24 h, Rat, Male / female, Experimental value, Dermal, 15 day(s))
ATE US (oral)	424 mg/kg body weight

Skin corrosion/irritation : Not classified

ethanol (64-17-5)	
pH	7 (789 g/l, 20 °C)

Serious eye damage/irritation : Not classified

ethanol (64-17-5)	
pH	7 (789 g/l, 20 °C)

Respiratory or skin sensitization : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

Germ cell mutagenicity : Suspected of causing genetic defects.

Carcinogenicity : May cause cancer.

ethanol (64-17-5)	
IARC group	1 - Carcinogenic to humans

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

ethanol (64-17-5)	
LOAEL (oral,rat,90 days)	3200 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (oral,rat,90 days)	1730 mg/kg body weight Animal: rat, Animal sex: male, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents), Remarks on results: other:
NOAEL (subchronic,oral,animal/male,90 days)	< 9700 mg/kg body weight Animal: mouse, Animal sex: male, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)
NOAEL (subchronic,oral,animal/female,90 days)	> 9400 mg/kg body weight Animal: mouse, Animal sex: female, Guideline: EPA OPPTS 870.3100 (90-Day Oral Toxicity in Rodents)

Aspiration hazard : Not classified

ethanol (64-17-5)	
Viscosity, kinematic	1.6 mm ² /s (20 °C)

cobalt(II)sulfate, heptahydrate (10026-24-1)	
Viscosity, kinematic	Not applicable

Potential Adverse human health effects and symptoms : Based on available data, the classification criteria are not met.

Symptoms/effects : Suspected of causing genetic defects.

Symptoms/effects after inhalation : May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause cancer by inhalation.

Symptoms/effects after skin contact : May cause an allergic skin reaction.

Symptoms/effects after eye contact : None under normal conditions.

Symptoms/effects after ingestion : None under normal conditions.

Chronic symptoms : May damage fertility or the unborn child.

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12 Ecological information

12.1. Ecotoxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment. Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Ecology - water	: Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Hazardous to the aquatic environment, short-term (acute)	: Harmful to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Harmful to aquatic life with long lasting effects.

ethanol (64-17-5)	
LC50 - Fish [1]	15300 mg/l (US EPA, 96 h, Pimephales promelas, Flow-through system, Fresh water, Experimental value, Lethal)
EC50 - Crustacea [1]	9300 mg/l (48 h, Daphnia magna, Pure substance)
EC50 72h - Algae [1]	275 mg/l (Equivalent or similar to OECD 201, Chlorella vulgaris, Static system, Fresh water, Experimental value, Growth rate)
EC50 96h - Algae [1]	≈ 22000 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
ErC50 algae	275 mg/l Source: ECHA
NOEC (chronic)	9.6 mg/l Test organisms (species): Daphnia magna Duration: '9 d'

cobalt(II)sulfate, heptahydrate (10026-24-1)	
LC50 - Fish [1]	1.512 mg/l (ASTM, 96 h, Oncorhynchus mykiss, Flow-through system, Fresh water, Read-across, Anhydrous form)
ErC50 algae	0.2 mg/l (OECD 201: Alga, Growth Inhibition Test, 72 h, Pseudokirchneriella subcapitata, Static system, Fresh water, Experimental value, Anhydrous form)

12.2. Persistence and degradability

Co-NTA Resin	
Persistence and degradability	May cause long-term adverse effects in the environment.

ethanol (64-17-5)	
Persistence and degradability	Not established.
Biochemical oxygen demand (BOD)	0.8 – 0.967 g O ₂ /g substance
Chemical oxygen demand (COD)	1.7 g O ₂ /g substance
ThOD	2.1 g O ₂ /g substance
BOD (% of ThOD)	0.43

cobalt(II)sulfate, heptahydrate (10026-24-1)	
Persistence and degradability	Biodegradability: not applicable.
Chemical oxygen demand (COD)	Not applicable (inorganic)
ThOD	Not applicable (inorganic)

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

12.3. Bioaccumulative potential

Co-NTA Resin	
Bioaccumulative potential	Not established.
ethanol (64-17-5)	
Partition coefficient n-octanol/water (Log Pow)	-0.35 (Experimental value, Equivalent or similar to OECD 107, 24 °C)
Bioaccumulative potential	Not established.
cobalt(II)sulfate, heptahydrate (10026-24-1)	
BCF - Other aquatic organisms [1]	2240 (3 day(s), Cyclotella, Static system, Fresh water, Read-across, Anhydrous form)
Bioaccumulative potential	Potential for bioaccumulation ($500 \leq \text{BCF} \leq 5000$).

12.4. Mobility in soil

ethanol (64-17-5)	
Surface tension	22.31 mN/m (20 °C, 100 %)
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.2 (log Koc, Experimental value)
Ecology - soil	Highly mobile in soil.
cobalt(II)sulfate, heptahydrate (10026-24-1)	
Ecology - soil	No (test)data on mobility of the substance available.

12.5. Other adverse effects

Ozone	: Not classified
Fluorinated greenhouse gases	: No
Other information	: Avoid release to the environment.

SECTION 13 Disposal considerations

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Waste treatment methods.
Sewage disposal recommendations	: Disposal must be done according to official regulations.
Product/Packaging disposal recommendations	: Dispose in a safe manner in accordance with local/national regulations. Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation. Disposal must be done according to official regulations.
Additional information	: Handle empty containers with care because residual vapors are flammable. Flammable vapors may accumulate in the container. Do not re-use empty containers.
Ecological waste information	: Avoid release to the environment.

SECTION 14 Transport information

In accordance with DOT / TDG / IATA

14.1. UN number

Not regulated for transport

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

14.2. UN Proper Shipping Name

Proper Shipping Name (DOT) : Not regulated
Proper Shipping Name (TDG) : Not regulated
Proper Shipping Name (IATA) : Not regulated

14.3. Transport hazard class(es)

DOT
Transport hazard class(es) (DOT) : Not regulated

TDG
Transport hazard class(es) (TDG) : Not regulated

IATA
Transport hazard class(es) (IATA) : Not regulated

14.4. Packing group

Packing group (DOT) : Not regulated
Packing group (TDG) : Not regulated
Packing group (IATA) : Not regulated

14.5. Environmental hazards

Other information : No supplementary information available.

14.6. Transport in bulk

Not applicable

14.7. Special precautions for user

DOT
Not regulated

TDG
Not regulated

IATA
Not regulated

SECTION 15 Regulatory information

15.1. Federal regulations

Commercial status of components according to the United States Environmental Protection Agency's Toxic Substances Control Act (TSCA):

Name	CAS-No.	Listing	Commercial status	Flags
ethanol	64-17-5	Present		
cobalt(II)sulfate, heptahydrate	10026-24-1	Not present	-	

15.2. International regulations

CANADA

ethanol (64-17-5)

Listed on the Canadian DSL (Domestic Substances List)

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

EU-Regulations

No additional information available

National regulations

ethanol (64-17-5)
Listed on IARC (International Agency for Research on Cancer) Listed on INSQ (Mexican National Inventory of Chemical Substances)

cobalt(II)sulfate, heptahydrate (10026-24-1)
Listed on IARC (International Agency for Research on Cancer)

15.3. State regulations

cobalt(II)sulfate, heptahydrate (10026-24-1)					
U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)	Maximum allowable dose level (MADL)
Yes	No	No	No		

SECTION 16 Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 11/24/2025
Date of issue : 2/25/2015
Other information : None.

Full text of hazard classes and H-statements	
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H317	May cause an allergic skin reaction
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects

Abbreviations and acronyms	
ACGIH	American Conference of Government Industrial Hygienists
ADN	European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
ADR	European Agreement concerning the International Carriage of Dangerous Goods by Road
ATE	Acute Toxicity Estimate

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms	
BCF	Bioconcentration factor
BLV	Biological limit value
BOD	Biochemical oxygen demand (BOD)
CAS-No.	Chemical Abstract Service number
CLP	Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
COD	Chemical oxygen demand (COD)
CSA	Chemical safety assessment
DMEL	Derived Minimal Effect level
DNEL	Derived-No Effect Level
EC-No.	European Community number
EC50	Median effective concentration
ED	Endocrine disruptor
EN	European Standard
EWC	European waste catalogue
IARC	International Agency for Research on Cancer
IATA	International Air Transport Association
IMDG	International Maritime Dangerous Goods
LC50	Median lethal concentration
LD50	Median lethal dose
LOAEL	Lowest Observed Adverse Effect Level
Log Kow	Partition coefficient n-octanol/water (Log Kow)
Log Pow	Partition coefficient n-octanol/water (Log Pow)
MAK	maximum workplace concentration
NOAEC	No-Observed Adverse Effect Concentration
NOAEL	No-Observed Adverse Effect Level
NOEC	No-Observed Effect Concentration
N.O.S.	Not Otherwise Specified
OECD	Organisation for Economic Co-operation and Development
OEL	Occupational Exposure Limit
OSHA	Occupational Safety & Health Administration
PBT	Persistent Bioaccumulative Toxic
PNEC	Predicted No-Effect Concentration
PPE	Personal protection equipment
RID	Regulations concerning the International Carriage of Dangerous Goods by Rail
SDS	Safety Data Sheet
STP	Sewage treatment plant

Co-NTA Resin

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Abbreviations and acronyms	
TF	Technical function
ThOD	Theoretical oxygen demand (ThOD)
TLM	Median Tolerance Limit
TWA	Time Weighted Average
VOC	Volatile Organic Compounds
vPvB	Very Persistent and Very Bioaccumulative
UFI	Unique Formula Identifier

Safety Data Sheet (SDS), USA

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.